LM1117 3.3V/5.0V Power Supply Module

FEATURES

- LM1117 3.3V/5.0V Power Supply Module
- Input Voltage Source: 5.0V USB Powered
- Output Voltage: 3.3V or 5.0V
- Output Current: Max. 500mA
- Power Indicator LED
- Very Small Size Power Supply Module



APPLICATIONS

- Simple 3.3V/5.0V Output Linear Regulator
- Power Supply for prototype device
- Power Supply for Arduino

ORDERING INFORMATION

Part Number	MLS1117-06
Device	LM1117 3.3V/5.0V Power Supply Module
Package	Assembled Module (21mm X 18mm)

DESCRIPTION

The LM1117 3.3V/5.0V Power Supply Module is a simple board that accepts a 5.0V input and provides either a regulated 3.3V output or a direct 5.0V pass-through output.

APPLICATION GUIDE

The power dissipation of the LM1117 Power Supply Module is internally limited. Small sized PCB and thermal resistance of IC package have limited the power dissipation of the module.

Depending on the output current condition, 500mA full loading is not might possible due to the internally limited power dissipation.

LM1117 3.3V/5.0V Power Supply Module

SCHEMATICS



LAYOUT

Top



Bottom

LM1117 3.3V/5.0V Power Supply Module

SIZE INFORMATION



PRODUCT IMAGE



LM1117 3.3V/5.0V Power Supply Module

I/O PORT CONFIGURATION AND DESCRIPTION



Designator	Port Name	Port Description
1	Input Connector	Input 5.0V USB Powered
2	Output Connector	Output 3.3V or 5.0V
3	Output Selection	Selectable 3.3V / 5.0V by using pin jumper

REVISION NOTICE

The description in this datasheet is subject to change without any notice to describe its electrical characteristics properly.

1A L.D.O VOLTAGE REGULATOR LM1117GS

FEATURES

- Output Current up to 1A
- Dropout Voltage is 1.2V at Output current
- Three Terminal Adjustable(ADJ) or Fixed 1.2V, 1.5V, 1.8V, 2.5V, 3.3V, and 5.0V
- Line Regulation typically at 0.1% typ.
- Load Regulation typically at 0.2% typ.
- Internal Current and Thermal Protection
- Surface Mount Package SOT-223-3L
- Moisture Sensitivity Level 3

SOT-223-3L

APPLICATIONS

- Active SCSI Terminators
- Portable/ Plan Top/ Notebook Computers
- High Efficiency Linear Regulators
- SMPS Post Regulators
- Mother B/D Clock Supplies
- Disk Drives
- Battery Chargers

ORDERING INFORMATION

Device	Package
LM1117GS-ADJ	SOT-223-3L
LM1117GS-x.x	

x.x: Output Voltage = 1.2V, 1.5V, 1.8V, 2.5V, 3.3V, and 5.0V

DESCRIPTION

The LM1117GS is a low power positive-voltage regulator designed to meet 1A output current. This device is an excellent choice for use in battery-powered applications, as active terminators for the SCSI bus, and portable computers. The LM1117GS features very low quiescent current and very low dropout voltage of 1.2V at a full load and lower as output current decreases. LM1117GS is available as an adjustable or fixed 1.2V, 1.5V, 1.8V, 2.5V, 3.3V, and 5.0V output voltages. The LM1117GS is offered in a 3-pin surface mount package SOT-223-3L. The output capacitor of 10μF or larger is needed for output stability of LM1117GS as required by most of the other regulator circuits.

ABSOLUTE MAXIMUM RATINGS

CHARACTERISTIC	SYMBOL	MIN.	MAX.	UNIT
Input Supply Voltage	V_{IN}	-	20	V
Lead Temperature (Soldering, 10 seconds)	T_{SOL}	-	260	°C
Storage Temperature Range	T_{STG}	−65	150	°C
Operating Junction Temperature Range	T_{JOPR}	−40	125	°C

ORDERING INFORMATION

V_{OUT}	Package	Order No.	Supplied As	Status
ADJ	SOT-223-3L	LM1117GS-ADJ	Tape & Reel	Active
1.2V	SOT-223-3L	LM1117GS-1.2	Tape & Reel	Active
1.5V	SOT-223-3L	LM1117GS-1.5	Tape & Reel	Active
1.8V	SOT-223-3L	LM1117GS-1.8	Tape & Reel	Active
2.5V	SOT-223-3L	LM1117GS-2.5	Tape & Reel	Active
3.3V	SOT-223-3L	LM1117GS-3.3	Tape & Reel	Active
5.0V	SOT-223-3L	LM1117GS-5.0	Tape & Reel	Active

PIN CONFIGURATION



SOT-223-3L

PIN DESCRIPTION

Pin No.	Pin Name	Pin Function
1	ADJ / GND	Adjustable or Ground (Fixed Version)
2	VOUT	Output Voltage
3	VIN	Input Voltage

TYPICAL APPLICATION CIRCUITS

< Fixed Version>



<Adjustable Version>



ELECTRICAL CHARACTERISTICS

For ADJ Output Voltage (T_J=25°C, C_{OUT} = 10µF unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_{REF}	Reference Voltage	V_{IN} = 5V, I_O = 10mA	1.238	1.250	1.262	V
V_{REF}	Reference Voltage	I_O = 10mA to 1A, V_{IN} - V_{REF} = 1.5V to 13.75V (T_J = -40°C ~ 125°C)	1.219		1.281	V
ΔV_{LINE}	Line Regulation	I_O = 10mA , V_{IN} - V_{REF} = 1.5V to 12V		0.1	0.2	%
ΔV_{LOAD}	Load Regulation	I_O = 10mA to 1A, V_{IN} - V_{REF} = 2V		0.2	0.4	%
V_{IN}	Operating Input Voltage				12	V
I_{ADJ}	Adjustment pin Current	V_{IN} - V_{REF} = 1.5V to 12V, I_O = 100mA		50	120	µA
ΔI_{ADJ}	Adjustment Pin Current Change	V_{IN} - V_{REF} = 1.5V to 12V, I_O = 100mA to 1A		0.5	5	µA
$I_{O(MIN)}$	Minimum Load Current	V_{IN} = 5V, V_{REF} = 0V		2	7	mA
I_{GND}	Ground Pin Current	V_{IN} = V_O +1.5V I_O =10 mA to 1A		5	10	mA
I_O	Current Limit	V_{IN} - V_{REF} = 5V	1000			mA
eN	Output Noise (%V_O)	B = 10Hz to 10kHz, T_J = 25°C		0.003		%
SVR	Supply Voltage Rejection	I_O = 1A, f = 120Hz, V_{IN} - V_{REF} = 3V, V_{RIPPLE} = 1V_{PP}	60	75		dB

For 1.2V Output Voltage (T_J=25°C, C_{OUT} = 10µF unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_O	Output Voltage	V_{IN} = 2.7V, I_O = 10mA	1.176	1.200	1.224	V
V_O	Output Voltage	V_{IN} = 2.7V to 12V, I_O = 0mA to 1A (T_J = -40°C ~ 125°C)	1.152		1.248	V
ΔV_{LINE}	Line Regulation	I_O = 10mA , V_{IN} = 2.7V to 12V		0.1	0.2	%
ΔV_{LOAD}	Load Regulation	I_O = 10mA to 1A, V_{IN} = 3.2V		0.2	0.4	%
V_{IN}	Operating Input Voltage				12	V
I_{GND}	Ground Pin Current	V_{IN} = V_O +1.5V I_O =10 mA to 1A		5	10	mA
I_O	Current Limit	V_{IN} - V_O = 5V	1000			mA
eN	Output Noise (%V_O)	B = 10Hz to 10kHz, T_J = 25°C		0.003		%
SVR	Supply Voltage Rejection	I_O = 1A, f = 120Hz, V_{IN} - V_O = 1.5V, V_{RIPPLE} = 1V_{PP}	60	75		dB

For 1.5V Output Voltage (T_J=25°C, C_{OUT} = 10µF unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_O	Output Voltage	V_{IN} = 3.0V, I_O = 10mA	1.485	1.5	1.515	V
V_O	Output Voltage	V_{IN} = 3.0V to 12V, I_O = 0mA to 1A (T_J = -40°C ~ 125°C)	1.470		1.530	V
ΔV_{LINE}	Line Regulation	I_O = 10mA , V_{IN} = 3.0V to 12V		0.1	0.2	%
ΔV_{LOAD}	Load Regulation	I_O = 10mA to 1A, V_{IN} = 3.5V		0.2	0.4	%
V_{IN}	Operating Input Voltage				12	V
I_{GND}	Ground Pin Current	V_{IN} = V_O +1.5V I_O =10 mA to 1A		5	10	mA
I_O	Current Limit	V_{IN} - V_O = 5V	1000			mA
eN	Output Noise(%V_O)	B = 10Hz to 10kHz, T_J = 25°C		100		µV
SVR	Supply Voltage Rejection	I_O = 1A, f = 120Hz, V_{IN} - V_O = 3V, V_{RIPPLE} = $1V_{PP}$	60	75		dB

For 1.8V Output Voltage (T_J=25°C, C_{OUT} = 10µF unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_O	Output Voltage	V_{IN} = 3.3V, I_O = 10mA	1.782	1.8	1.818	V
V_O	Output Voltage	V_{IN} = 3.3V to 12V, I_O = 0mA to 1A (T_J = -40°C ~ 125°C)	1.764		1.836	V
ΔV_{LINE}	Line Regulation	I_O = 10mA , V_{IN} = 3.3V to 12V		0.1	0.2	%
ΔV_{LOAD}	Load Regulation	I_O = 10mA to 1A, V_{IN} = 3.8V		0.2	0.4	%
V_{IN}	Operating Input Voltage				12	V
I_{GND}	Ground Pin Current	V_{IN} = V_O +1.5V I_O =10 mA to 1A		5	10	mA
I_O	Current Limit	V_{IN} - V_O = 5V	1000			mA
eN	Output Noise(%V_O)	B = 10Hz to 10kHz, T_J = 25°C		100		µV
SVR	Supply Voltage Rejection	I_O = 1A, f = 120Hz, V_{IN} - V_O = 3V, V_{RIPPLE} = $1V_{PP}$	60	75		dB

For 2.5V Output Voltage (T_J=25°C, C_{OUT} = 10µF unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_O	Output Voltage	V_{IN} = 4.0V, I_O = 10mA	2.475	2.5	2.525	V
V_O	Output Voltage	V_{IN} = 4.0V to 12V, I_O = 0mA to 1A (T_J = -40°C ~ 125°C)	2.450		2.550	V
ΔV_{LINE}	Line Regulation	I_O = 10mA , V_{IN} = 4.0V to 12V		0.1	0.2	%
ΔV_{LOAD}	Load Regulation	I_O = 10mA to 1A, V_{IN} = 4.5V		0.2	0.4	%
V_{IN}	Operating Input Voltage				12	V
I_{GND}	Ground Pin Current	V_{IN} = V_O +1.5V I_O =10 mA to 1A		5	10	mA
I_O	Current Limit	V_{IN} - V_O = 5V	1000			mA
eN	Output Noise(%V_O)	B = 10Hz to 10kHz, T_J = 25°C		100		µV
SVR	Supply Voltage Rejection	I_O = 1A, f = 120Hz, V_{IN} - V_O = 3V, V_{RIPPLE} = $1V_{PP}$	60	75		dB

For 3.3V Output Voltage (T_J=25°C, C_{OUT} = 10µF unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_O	Output Voltage	V_{IN} = 4.8V, I_O = 10mA	3.267	3.3	3.333	V
V_O	Output Voltage	V_{IN} = 4.8V to 12V, I_O = 0mA to 1A (T_J = -40°C ~ 125°C)	3.234		3.366	V
ΔV_{LINE}	Line Regulation	I_O = 10mA , V_{IN} = 4.8V to 12V		0.1	0.2	%
ΔV_{LOAD}	Load Regulation	I_O = 10mA to 1A, V_{IN} = 5.3V		0.2	0.4	%
V_{IN}	Operating Input Voltage				12	V
I_{GND}	Ground Pin Current	V_{IN} = V_O +1.5V I_O =10 mA to 1A		5	10	mA
I_O	Current Limit	V_{IN} - V_O = 5V	1000			mA
eN	Output Noise(%V_O)	B = 10Hz to 10kHz, T_J = 25°C		100		µV
SVR	Supply Voltage Rejection	I_O = 1A, f = 120Hz, V_{IN} - V_O = 3V, V_{RIPPLE} = $1V_{PP}$	60	75		dB

For 5.0V Output Voltage (T_J=25°C, C_{OUT} = 10µF unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_O	Output Voltage	V_{IN} = 6.5V, I_O = 10mA	4.950	5.0	5.050	V
V_O	Output Voltage	V_{IN} = 6.5V to 15V, I_O = 0mA to 1A (T_J = -40°C ~ 125°C)	4.900		5.100	V
ΔV_{LINE}	Line Regulation	I_O = 10mA , V_{IN} = 6.5V to 15V		0.1	0.2	%
ΔV_{LOAD}	Load Regulation	I_O = 10mA to 1A, V_{IN} = 7.0V		0.2	0.4	%
V_{IN}	Operating Input Voltage				15	V
I_{GND}	Ground Pin Current	V_{IN} = V_O +1.5V I_O =10 mA to 1A		5	10	mA
I_O	Current Limit	V_{IN} - V_O = 5V	1000			mA
eN	Output Noise(%V_O)	B = 10Hz to 10kHz, T_J = 25°C		100		µV
SVR	Supply Voltage Rejection	I_O = 1A, f = 120Hz, V_{IN} - V_O = 3V, V_{RIPPLE} = 1V_{PP}	60	75		dB

For All Output Voltage (T_J=25°C, C_{OUT} = 10µF unless otherwise specified)

SYMBOL	PARAMETER	CONDITIONS	MIN.	TYP.	MAX.	UNIT
V_D	Dropout Voltage	I_O = 100mA		1.0	1.1	V
		I_O = 500mA		1.1	1.2	V
		I_O = 1A		1.2	1.3	V
	Temperature Stability			0.5		%
	Long Term Stability	1000 hrs, T_J = 125°C		0.3		%
	Thermal Regulation	T_A = 25°C 30ms Pulse		0.003		%/W
T_{SD}	Thermal Shutdown	Junction Temperature		165		°C
$T_{SD(HYS)}$	Thermal Shutdown Hysteresis			10		°C

TYPICAL OPERATING CHARACTERISTICS



OUTPUT VOLTAGE CHANGE VS TEMPERATURE



DROPOUT VOLTAGE VS OUTPUT CURRENT



ADJ PIN CURRENT VS TEMPERATURE



QUIESCENT CURRENT CHANGE VS TEMPERATURE

APPLICATION CIRCUITS



Fig.1 300mA Current Output



Fig.2 Typical Adjustable Regulator



Fig.3 Negative Supply



Fig.4 Voltage Regulator with Reference



Fig.5 Battery Backed-up Regulated Supply

APPLICATION INFORMATION

The LM1117GS can deliver a continuous current of 1A over the full operating junction temperature range. However, the output current is limited by the restriction of power dissipation which differs from packages. A heat sink may be required depending on the maximum power dissipation and maximum ambient temperature of application. With respect to the applied package, the maximum output current of 1A may be still undeliverable due to the restriction of the power dissipation of LM1117GS. Under all possible conditions, the junction temperature must be within the range specified under operating conditions. The temperatures over the device are given by:

$$T_C = T_A + P_D \times \theta_{CA} \quad / \quad T_J = T_C + P_D \times \theta_{JC} \quad / \quad T_J = T_A + P_D \times \theta_{JA}$$

where T_J is the junction temperature, T_C is the case temperature, T_A is the ambient temperature, P_D is the total power dissipation of the device, θ_{CA} is the thermal resistance of case-to-ambient, θ_{JC} is the thermal resistance of junction-to-case, and θ_{JA} is the thermal resistance of junction to ambient. The total power dissipation of the device is given by:

$$P_D = P_{IN} - P_{OUT} = (V_{IN} \times I_{IN}) - (V_{OUT} \times I_{OUT})$$
$$= (V_{IN} \times (I_{OUT} + I_{GND})) - (V_{OUT} \times I_{OUT}) = (V_{IN} - V_{OUT}) \times I_{OUT} + (V_{IN} \times I_{GND})$$

where I_{GND} is the operating ground current of the device which is specified at the Electrical Characteristics. The maximum allowable temperature rise (T_{Rmax}) depends on the maximum ambient temperature (T_{Amax}) of the application, and the maximum allowable junction temperature (T_{Jmax}):

$$T_{Rmax} = T_{Jmax} - T_{Amax}$$

The maximum allowable value for junction-to-ambient thermal resistance, θ_{JA}, can be calculated using the formula:

$$\theta_{JA} = T_{Rmax} / P_D = (T_{Jmax} - T_{Amax}) / P_D$$

LM1117GS is available in SOT-223-3L packages. The thermal resistance depends on amount of copper area or heat sink, and on air flow. If the maximum allowable value of θ_{JA} calculated above is over 140°C/W for SOT-223-3L package, no heat sink is needed since the package can dissipate enough heat to satisfy these requirements. If the value for allowable θ_{JA} falls near or below these limits, a heat sink or proper area of copper plane is required. In summary, the absolute maximum ratings of thermal resistances are as follow:

Characteristic	Symbol	Rating	Unit
Thermal Resistance Junction-To-Ambient / SOT-223-3L	θ_{JA}-SOT-223	140	°C/W
Thermal Resistance Junction-To-Case / SOT-223-3L	θ_{JC}-SOT-223	18	°C/W

No heat sink / No air flow / No adjacent heat source / T_A=25°C

REVISION NOTICE

The description in this datasheet is subject to change without any notice to describe its electrical characteristics properly.